

# HETH-TVT

## LED VAPOR TIGHT

LED Vapor Tight, Select (3-Wattages + 3-CCT), 130 lm/W, UL 1598 Wet Location Rated, Dimmable + Smart Ready

### FEATURES

Lumen Output	4420 to 11700 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3500K, 4000K, 5000K)
IP Rating	UL 1598 Wet Location
Size	4-FT, 8-FT
Warranty	7 Years

### APPLICATIONS

Premium indoor luminaire for hanging or surface mounting in ceiling spaces less than 25 feet. Suitable for harsh environments, manufacturing, production, processing, R&D, parking garages, stairwells, and wet locations.

### CONSTRUCTION

Manufactured for durability with injection molded polycarbonate to resist corrosion, discoloration, and scratching. Stainless steel clips lock the lens cover to resist dust, moisture and vapors. UL 1598 Wet Location rated.

### ELECTRICAL

Input voltage 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and Tunable 3-Wattage (4-FT, 34W, 38W, 45W) or (8-FT, 65W, 75W, 90W). Operating temperatures -40°F to 104°F (-40°C to 40°C).

### MOUNTING

Aluminum Surface Mount clips standard. Optional 10-FT Aircraft Cables for hanging available.

### OPTICS

Anti-UV Frosted Prismatic Polycarbonate Lens.

### LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, and RoHS compliant.

### WARRANTY

7 year exclusive limited warranty.

4-FT and 8-FT Tunable Models




### TUNABLE

#### CORRELATED COLOR TEMPERATURES (CCT)

3500K

4000K

5000K



**SPECIFICATIONS**
**ENERGY DATA**

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: Select (34W, 38W, 45W), Select (65W, 75W, 90W)

Power Factor: &gt;0.9

Total Harmonic Distortion (THD): &lt;10%

Operating Temperature: -40°F to 104°F (-40°C to 40°C)

**LIGHTING DATA**

Lumens: Select [4420 (34W), 4940 (38W), 5850 (45W)] or Select [8450 (65W), 9750 (75W), 11700 (90W)]

Lumens Per Watt: 130 lm/W

Color Correlated Temperature (CCT): Select (3500K, 4000K, 5000K)

Dimmable: 0-10V

Color Rendering Index (CRI): &gt;82

L70: 75000 hours

**ORDERING INFORMATION**

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions	Weight
HETH-TVT-4F-45W	4-FT	(34W	120-277V	0.28A@120V, 0.12A@277V	4420	130 lm/W	(3500K, 4000K, 5000K)	0-10V	Lt.Gray	47.20"L x 3.50"W x 3.10"H	4.41 lbs
		38W		0.32A@120V, 0.14A@277V	4940						
		45W)		0.38A@120V, 0.16A@277V	5850						
HETH-TVT-8F-90W	8-FT	(65W	120-277V	0.54A@120V, 0.23A@277V	8450	130 lm/W	(3500K, 4000K, 5000K)	0-10V	Lt.Gray	94.50"L x 3.50"W x 3.10"H	7.72 lbs
		75W		0.63A@120V, 0.27A@277V	9750						
		90W)		0.75A@120V, 0.32A@277V	11700						

**Mount**


AC-10	Pair of 10-FT Aircraft Cables
(Blank)	Surface Mount Clips (Standard)

**ORDERING GUIDE**


HETH	TVT	4F	45W	AC-10
HETH	Group	Size	Wattage	Mount

**PHYSICAL DIMENSIONS**
**4-FT Model**

47.20"L x 3.50"W x 3.10"H


**8-FT Model**

94.50"L x 3.50"W x 3.10"H


**HETH-TVT-4F-45W(3500K)**
