

HETH-TLS/LSPT

COMMERCIAL & INDUSTRIAL INDOOR LUMINAIRE

Illuminate indoor areas day and night with HETH. Easily switch settings between lighting hues and input wattage to create that perfect glow. Engineered for balanced LED lumen output with long-rated life. Smart Ready for daylight, bi-level dimming, motion and occupancy sensor functions.

Features

Sizes	4 ft and 8 ft
Finish	Pure White Semi-Gloss
Diffuser	Anti-UV Frosted Polycarbonate Lens
Rated Life	75000 hours
Warranty	7 years

Construction

Manufactured for durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration and scratching.

Applications

Primary use as low bay luminaires for commercial and industrial buildings. Pendant or surface-mounted fixtures specifically for indoor ceiling spaces less than 25 feet.

Listings

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

Warranty

7 year exclusive limited warranty.



Performance

Wattage	See ordering information.
Voltage	120-277V
Frequency	50/60 Hz
Efficacy	130 lm/W
CCT	Tunable (3500K, 4000K, or 5000K)
CRI	≥ 80
Power Factor	> 0.9
THD	< 20%
Operating Temp.	-20°C to 40°C (-4°F to 104°F)
Dimming	0-10V



ORDERING INFORMATION

Model No.	Size	Wattage (W)	Voltage (V)	CCT (K)	Light Output	Efficacy (lm/w)	Rated Life
HETH-TLS-4-40W	4 ft	25	120-277V	3500K, 4000K, 5000K	3250 lm	130 lm/W	75000 hrs
		30	120-277V	3500K, 4000K, 5000K	3900 lm	130 lm/W	75000 hrs
		40	120-277V	3500K, 4000K, 5000K	5200 lm	130 lm/W	75000 hrs
HETH-LSPT-8-65W	8 ft	54	120-277V	3500K, 4000K, 5000K	7020 lm	130 lm/W	75000 hrs
		60	120-277V	3500K, 4000K, 5000K	7800 lm	130 lm/W	75000 hrs
		65	120-277V	3500K, 4000K, 5000K	8450 lm	130 lm/W	75000 hrs