

HLV4

Spec-grade | Vertical Architectural LED Linear Surface Lighting

Ideal for locations with low ceilings or where fire ratings prevent recessed luminaires. It is integrated with ultra-thin semi-transparent vertical optics, enveloped in a signature sloping silhouette where the frame meets the optics. It enables designers to mount the luminaire on ceilings to enhance architectural styling or add a unique flair to the interior design of a space. With wattage selectable and CCT adjustable function, packing a powerful punch of up to 1600 lumen per foot with 90+CRI.

Features:

- 3 lengths & sloping silhouette
- Transparent optics
- Wattage selectable, up to 1600 lm/ft
- True color, 90+CRI
- CCT adjustable from 3000K, 3500K and 4000K

STRUCTURE:

Finish: Extruded aluminum housing with powder coat white finish or custom.

Optics: Ultra-thin semi-transparent vertical optics, enveloped in a signature sloping silhouette where the frame meets the optics.

ELECTRICAL:

Mini Internal LED Driver: It is powered by Class 2 high efficiency LED driver, with a standard 0-10V dimming which continuous dims to 10% that works with many types of controls. Tested Dimmers: Lutron Diva-Dvtv, Leviton IP-710-DL.

THD: <20%

Power Factor: >0.9

Input Voltage: Standard electronic drivers are UL recognized and available for 110-277V or 110-347V AC* input voltage.


LED System:

CRI: Minimum 90 color rendering index.


CCT: CCT adjustable from 3000K, 3500K and 4000K

LED: Minimum 50,000h with 87.8% of lumen maintenance in 25° C ambient temperature, in compliance with IES LM-80 testing measurements.

Environment: Damp rated for ambient operating temperature of -20°C to +40°C (-4° to +104°F).



DIMENSIONS



D9F : CFA5B79

AcXY	@b[h	K uM U Y	' \$\$\$?	') \$\$\$? fB @ 'Ei U]zVUjcbL (\$\$\$? fB @ 'Ei U]zVUjcbL
HLV4-ITW2F	2'	20W	1150lm/ft, 115lm/w	1250lm/ft, 125lm/w
HLV4-ITW3F	3'	20W/30W/40W Selectable	750~1500lm/ft, 115lm/w	800~1650lm/ft, 125lm/w
HLV4-ITW4F	4'	20W/30W/40W Selectable	550~1150lm/ft, 115lm/w	600~1250lm/ft, 125lm/w

*All efficacy is ±5% base on different CCT. Check the IES file to gain the accurate data.

*Make to Order means additional cost and/or lead time on customized fixtures may apply. Some fixtures require an MOQ. Please contact your sales rep for more information.

Job Name: _____

Type: _____

Part #: _____


Notes: _____

DFC8I 7H'CF89F=B; ; I =89'

9I Ua d'Y. 'HLV4!HK & 'fGi fZJWZ

HLV4	-	I	TW	(Surface)	
Product Series		Driver	CCT	Length & Wattage	Just to remark the mounting. Doesn't show in product label.
HLV4 Meta Surface Linear		I Internal Driver	TW CCT Adjustable 3000K/3500K/4000K	2F 2 Feet,20W QuickShip	
				3F 3 Feet,20W/30W/40W Selectable QuickShip	
				4F 4 Feet,20W/30W/40W Selectable QuickShip	

OPTIONAL ACCESSORIES

Mounting		Optional Function	
SMK Surface Mounting Kits QuickShip		EME Emergency Function (Only external 8w or 25w LED emergency driver with standard indicator available and need field-installed.) QuickShip	