

Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

# LSDLX50 PHOTOLUMINESCENT EXIT SIGN

■ The DLX50 is visible at 50 feet.

Photoluminescent letters, maintenance free, zero energy consumption, zero cost with no lamps or battery replacement. A fully recyclable green design.

Removable chevrons standard.

Red outline shown here with optional white body.



■ Installation: Surface, flag, ceiling

of fluorescent, metal halide or mercury vapor light on the face(s) of the sign required at all times during building occupancy.)

The DLX50 features thin, low profile construction with consistent, uniform illumination.

indoor



## SPECIFICATIONS INTERNAL

- The LSDLX50 is 100% reliable, there are no internal parts to fail. It is a non-toxic, non-radioactive low exit solution. The SEEDLX50 is visible at up to 50 feet.

## SPECIFICATIONS EXTERNAL

- Construction: ABS plastic with photoluminescent panel. The LSDLX50 can be used for high and/or low level installations and has a 25 year life expectancy. It is visible at 50 feet during a blackout condition. The LSDLX50 meets current building codes, NFPA Life Safety Code 101 and OSHA requirements; International Building Code 2009; International Fire Code 2009.

## SPECIFICATIONS ELECTRICAL

- CIRCUIT: Since there is no electricity required, the LSDLX50 is a safer signage solution, which saves on maintenance and energy costs.

## LISTINGS AND WARRANTY

- The LSDLX50 Series comes with a 10 to 20 year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.

## SPECIFICATIONS MECHANICAL

- The LSDLX50 series utilizes photoluminescent technology which absorbs and stores ambient light. It is a non-toxic, and non-radioactive low profile emergency lighting solution. The LSDLX50 features field adjustable chevrons and is constructed of ABS plastic with photoluminescent panel. The LSDLX50 is NON-TOXIC and NON-RADIOACTIVE which eliminates disposal fees.

## DIMENSIONS



A	B	C
8.75"	15.38"	.75"
222mm	391mm	19mm

## ORDERING INFORMATION

Sample Part Number: **LSDLX50-P2-B-UB**

SERIES	# OF FACES	FRAME COLOR	LETTER OUTLINE	MOUNTING
LSDLX50	P1 (single) P2 (double)	R (red) G (green) B (black) W (white)[1]	G (green) R (red)	UB (universal mounting bracket)

[1]NOTE: use for outline letters (green or red) only.

[2]NOTE: only available with white frame color.