

Job Name:	
Type:	
Part #:	
Notes:	

LSWLEZ

COMPACT WET LOCATION LED EXIT SIGN

STANDARD

OPTIONAL











FEATURES

Ultra bright, energy efficient, long-life Red or Green LED.

ILLUMINATION

• Ultra-bright, energy efficient long-lasting Red or Green LED

ELECTRICAL

- Dual 120/277 voltage standard.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- Long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LEDs and LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

HOUSING

- 5VA flame retardant, UV-stabilized polycarbonate in white, black or gray finish
- High impact resistant, UV-stabilized polycarbonate clear lens.
- Fully gasketed corrosion-resistant enclosure.
- Engineering grade silicone gasket.
- K/O's provided for conduit feed applications.
- EZ snap-out chevron directional indicators.

MOUNTING

- Polycarbonate mounting canopy included for top or end mount.
- Universal K/O pattern on back plate for wall mount.




OPTIONS

- SDT: Self-diagnostic test feature continually diagnoses unit's performance and test system to ensure reliable operation and to meet electrical and life safety codes
- 2C: Dual-circuit option on the AC-only unit enables it to be connected to two different (one acting as a s back-up to the other) supplies at the same time
- TP: Tamper-proof hardware helps prevent unauthorized access to the unit

LISTINGS AND WARRANTIES

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL listed for wet locations.

DIMENSIONS



Sample Part Number: LSWLEZ- 1-R-W-EM-TP

ORDERING INFORMATION

MODEL	# OF FACES	LETTER COLOR	HOUSING COLOR	BATTERY	OPTIONS
LSWLEZ	1 - Single Face 2 - Double Face	R - Red G - Green	W - White B - Black G - Gray	BLANK - AC Only EM - Emergency backup	SDT - Self Diagnostic TP - Tamper Proof 2C - Dual Circuit