

Job Name:	
Type:	
Part #:	
Notes:	

# **LSXST** STEEL LED EXIT SIGN



#### **ILLUMINATION**

• Ultra bright, energy efficient, long life Red or Green LED.

## **ELECTRICAL**

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### MOUNTING

- Mounting canopy included for top or end mount.
- Universal K/O pattern on back plate for wall mount.

### **HOUSING**


- Durable, powder-coated 20-gauge steel construction in white or black finish.
- Unique design allows double face conversion in the field.
- Field selectable steel knockout chevron directional indicators.

#### **OPTIONS**

 SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.



### **DIMENSIONS**



# LISTINGS AND WARRANTIES

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).

#### ORDERING INFORMATION

Special voltage options available. Check with your Lighting Representative.

1 Available only with EM units.

**MODEL** 

LSXST

# OF FACES

1 - Single Face 2 - Universal Single/ Double Face

**LETTER** COLOR

R - Red G - Green HOUSING **COLOR** 

W - White B - Black

**BATTERY** 

Blank - AC Only EM - Battery Backup

Sample Part Number: LSXST

**OPTIONS** 

SDT - Self-Diagnostics 1